

Alterm National Pty Ltd ABN 70 111 695 893
Material Safety Data Sheet

Page No.: 1/5
Last Revision Date: 22/1/2006
Version: 2.0

NO MORE SOLDER TERMITE PROOF SILICONE

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product Details

Product Name: NO MORE SOLDER TERMITE PROOF SILICONE
Other Product: Silicone Sealant (Termite Proof)
Company Product Name: 03306283
Proper Shipping Name: Not applicable
Recommended Use: Sealant and adhesive
Building materials, indoor/outdoor or confined space applications.
A one-part silicone sealant designed for sealing applications on Zinalume, galvanised iron, anodised aluminum, coated steel products, concrete, brick veneer, aerated concrete(AAC) & rigid PVC. Suitable for sanitary type of applications due to presence of mould inhibitor.

1.2 Company Details

Manufacturer/Supplier: Dow Corning Australia Pty Ltd/Alterm National Pty Ltd
Address: 3 Innovation Rd North Ryde NSW 2113 Australia
Telephone Number: 1300 360 732
Emergency Telephone Number: 1300 360 732

2. HAZARD IDENTIFICATION

- 2.1 Hazard Classification:** Hazardous Substance. Non-Dangerous Goods.
2.2 Risk Phrase(s) May cause sensitisation by skin contact.
2.3 Safety Phrase(s) Avoid contact with eyes.
Wear suitable protective clothing and gloves.
Use only in well-ventilated areas.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion %</u>
Hydrotreated middle petroleum distillates	64742-46-7	<10
Methyl tri(ethylmethylketoxime) silane	22984-54-9	<10
Methylethylketoxime	96-29-7	<10
Di(ethylmethylketoxime) methoxymethyl silane	83817-72-5	<10
Ingredients determined not to be hazardous to 100%		

4. FIRST AID MEASURES

4.1 First Aid Measures:

Ingestion: Get medical attention.
Eye: Immediately flush with water for 15 minutes.
Skin: Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Inhalation: Remove to fresh air. Get medical attention if ill effects persist.

Alterm National Pty Ltd
Material Safety Data Sheet

Page No.: 2/5
Last Revision Date: 22/1/2006
Version: 2.0

NO MORE SOLDER TERMITE PROOF SILICONE

4. FIRST AID MEASURES - cont'd

4.2 Medical Attention and Special Treatment Needed:

First Aid Facilities: None should be required.

Comments: Treat according to person's condition and specifics of exposure.

Note to Physicians: Treat symptomatically. For further information, the medical practitioner should contact Dow Corning Australia Pty Ltd.

5. FIRE FIGHTING MEASURES

5.1 Suitable Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO²), dry chemical or water spray. Water can be used to cool fire-exposed containers.

5.2 Hazards From Combustion Products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen oxides. Formaldehyde. Metal oxides.

5.3 Precautions For Fire Fighters and Special Protective Equipment: Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.

5.4 Hazchem Code: Not applicable.

6. ACCIDENTAL RELEASE MEASURES

6.1 Emergency Procedures: Not applicable

6.2 Methods and Materials for Containment and Clean Up Procedures: Observe all personal protective equipment recommendations described in this MSDS. If liked, material can be pumped, store recovered material in appropriate container. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents, or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the clean up of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

7.1 Precautions for Safe Handling: Use with adequate ventilation. Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control MEKO within exposure guidelines or use respiratory protection. Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control methyl alcohol exposures within exposure guidelines or use air supplied or self-contained breathing apparatus. Avoid skin and eye contact. Avoid breathing vapour. Keep container closed. Do not take internally. Remove contaminated clothing immediately. Exercise good industrial hygiene practice. Wash after handling, especially before eating drinking or smoking.

7.2 Conditions for Safe Storage: Use reasonable care and store away from oxidising materials. Keep container closed and store away from water or moisture.

Alterm National Pty Ltd

Material Safety Data Sheet

Page No.: 3/5
Last Revision Date: 22/1/2006
Version: 2.0

NO MORE SOLDER TERMITE PROOF SILICONE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Standards:

Ingredients

Exposure Limits

Hydrotreated middle petroleum distillates

Observe oil mist limits. OSHA PEL (final rule) and ACGIH TLV: TWA 5mg/m³; ACGIH STEL 10mg/m³
No biological limit allocated.

Methyl tri(ethylmethylketoxime) silane

See ethyl methyl ketoxime comments.
No biological limit allocated.

Methylethylketoxime

Vendor Guide: TWA 3 ppm, STEL 10 ppm. AIHA WEEL: TWA 10 ppm.
No biological limit allocated

Di(ethylmethylketoxime) methoxymethyl silane

See methyl alcohol and ethyl methyl ketoxime comments.
No biological limit allocated

Ethyl methyl ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within the following exposure guidelines: Vendor Guide: TWA 3 ppm, STEL 10 ppm. AIHA WEEL: TWA 10 ppm. Methyl alcohol forms on contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of Worksafe Australia: TWA 200 ppm, STEL, 250 ppm, skin absorption; OSHA PEL: TWA 200 ppm and ACGIH TLV-skin: TWA 200 ppm, STEL 250 ppm.

8.2 Engineering Controls:

Local Ventilation:

Recommended.

General Ventilation:

Recommended.

8.3 Personal Protective Equipment:

Respiratory:

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator:

Organic Vapour Type.

Hand:

Butyl Rubber. Natural Rubber. Neoprene Rubber (R). Nitrile Rubber.

Eye:

Use proper protection - safety glasses as a minimum.

Skin:

Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1	Physical Form:	Paste
9.2	Colour:	Grey
9.3	Odor:	Some odor
9.4	pH:	Not determined
9.5	Vapour Pressure @ 25°C:	Not determined
9.6	Vapour Density (air=1):	Not determined
9.7	Boiling Point:	Not determined
9.8	Melting Point:	Not determined
9.9	Solubility in Water:	Not determined
9.10	Specific Gravity @ 25°C:	0.985

Alterm National Pty Ltd

Material Safety Data Sheet

Page No.:4/5
Last Revision Date: 22/1/2006
Version: 2.0

NO MORE SOLDER TERMITE PROOF SILICONE

9. PHYSICAL AND CHEMICAL PROPERTIES - cont'd

9.11	Flash Point	Not applicable
9.12	Upper Flammability Limit:	Not determined
9.13	Lower Flammability Limit:	Not determined
9.14	Auto ignition Temperature:	Not determined
9.15	Viscosity:	Not determined

The above information is not intended for use in preparing product specifications. Contact Alterm National before writing specifications.

10. STABILITY AND REACTIVITY

10.1	Chemical Stability:	Stable.
10.2	Conditions to avoid:	None.
10.3	Incompatible Materials:	Can react with strong oxidising agents. Water, moisture, or humid air can cause hazardous vapours to form.
10.4	Hazardous Decomposition Products:	Carbon dioxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen oxides. Formaldehyde. Metal oxides.
10.5	Hazardous Reactions:	Hazardous polymerization will not occur

11. TOXICOLOGICAL INFORMATION

11.1	Possible Routes of Exposure	<input type="checkbox"/> Inhalation	<input checked="" type="checkbox"/> Skin Contact	<input checked="" type="checkbox"/> Skin Contact
11.2	Possible Health Effects:			
	<u>Acute</u>			
	Ingestions	Low ingestion hazard in normal use.		
	Eye:	Direct contact may cause mild irritation.		
	Skin:	May cause moderate irritation.		
	Inhalation:	Irritates respiratory passages very slightly. Vapor overexposure may cause drowsiness.		
	<u>Chronic</u>			
	Ingestion:	Repeated ingestion or swallowing large amounts may injure internally.		
	Skin:	Repeated skin contact may cause allergic skin reaction. Repeated or prolonged contact may cause de-fatting and drying of skin, which may result in skin irritation and dermatitis.		
	Inhalation:	Overexposure by inhalation may injure the following organs(s): Blood. Liver.		
	Other Health Hazard Information:	Contains Methyl Ethyl Ketoxime (MEKO). Male rodents exposed to MEKO vapor throughout their lifetime developed liver cancer. Additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.		

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

Alterm National Pty Ltd
Material Safety Data Sheet

Page No.: 5/5
Last Revision Date: 22/1/2006
Version: 2.0

NO MORE SOLDER TERMITE PROOF SILICONE

12. ECOLOGICAL INFORMATION

- | | |
|---|---|
| 12.1 Environmental Fate and Distribution: | Solid material, insoluble in water. No adverse effects are predicted. |
| 12.2 Ecotoxicity: | No adverse effects on aquatic organisms are predicted. |
| Bioaccumulation: | No bioaccumulation potential. |
| 12.3 Fate and Effects in Waste Water Treatment Plants: | No adverse effects on bacteria are predicted. |

13. DISPOSAL CONSIDERATIONS

- | | |
|---|---|
| 13.1 Disposal Method: | Disposal of in accordance with local regulations. |
| 13.2 Special Precautions for Landfill or Incineration: | None known. |

14. TRANSPORT INFORMATION

- | | |
|--------------------------------------|---------------------------------|
| 14.1 UN No. | Not applicable |
| 14.2 Proper Shipping Name: | Not applicable |
| 14.3 Class: | Not applicable |
| 14.4 Packing Group: | Not applicable |
| 14.5 Hazchem Code: | Not applicable |
| 14.6 Sea Transport (IMDG) | Not subject to IMDG code |
| 14.7 Air Transport (IATA-DGR) | Not subject to IATA regulations |

15. REGULATORY INFORMATION

- | | |
|--|---|
| 15.1 SUSDP Poisons Schedule Number: | None allocated. |
| 15.2 Prohibition/Licensing Requirements: | There are no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation. |
| 15.3 Industrial Chemicals (Notification and Assessment) Act 1989: | All ingredients listed or exempt. |
| 15.4 Chemical Inventories | |
| IECSC: | All ingredients listed or exempt. |
| KECL: | All ingredients listed, exempt, or notified. |
| PICCS: | All ingredients listed or exempt. |
| EINECS: | Not determined |
| TSCA: | Not determined |
| MITI: | Not determined |
| DSL: | Not determined |

16. OTHER INFORMATION

- | | |
|-----------------------|-------------------------------------|
| Contact Point: | Product Safety Manager 1300 360 732 |
| Prepared by: | Dow Corning Australia Pty Ltd |

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this Company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.